

IN THE CLAIMS

Please cancel claims 1-15(cancelled) and replace with the following new claims:

16. (new) A gasket for molding a spectacle plastic lens, characterized by comprising

a cylindrical gasket main body in which a first mold with a lens molding surface that forms one lens surface of the spectacle plastic lens and a second mold with a lens molding surface that forms the other lens surface of the spectacle plastic lens are incorporated to be spaced apart from each other at a predetermined gap, and

an elastic projecting band which integrally projects on an inner circumferential wall of said gasket main body throughout an entire circumference,

wherein said projecting band includes a ring-like proximal end portion which projects from the inner circumferential wall of said gasket main body and a tapered distal end portion which is closer to an axial direction of said gasket main body than the proximal end portion, and

when at least one of said first mold and said second mold is incorporated, said gasket main body holds said one mold by pressing an outer circumferential surface of said one mold in a diameter-reducing direction with a restoring force of elastic deformation in a diameter-increasing direction, and a vertex of the distal end portion of said projecting band comes into

contact with the lens molding surface of said one mold by flexing the proximal end

portion of said projecting band.

17. (new) A gasket for molding a plastic lens according to claim 16, characterized in that said proximal end portion of said projecting band is perpendicular to an axis of said gasket main body.

18. (new) A gasket for molding a plastic lens according to claim 16, characterized in that said proximal end portion of said projecting band inclines toward said one mold.

19. (new) A gasket for molding a plastic lens according to claim 16, characterized in that said distal end portion of said projecting band is substantially parallel to an axis of said gasket main body.

20. (new) A gasket for molding a plastic lens according to claim 16, characterized in that said distal end portion and proximal end portion of said projecting band are connected to each other in a bent manner.

21. (new) A gasket for molding a plastic lens according to claim 16, characterized in that the nearer toward said distal end portion, the closer said projecting band becomes to the axial direction gradually.

22. (new) A gasket for molding a plastic lens according to claim 16, characterized in that said projecting band comprises two projecting bands to correspond to said first mold and said second mold.

23. (new) A gasket for molding a plastic lens according to claim 16,

characterized in that

said gasket main body further comprises a positioning projection which integrally projects on said inner circumferential surface, and

said positioning projection positions said one mold in said gasket main body when a peripheral portion of said one mold on a lens molding surface side comes into contact with said positioning projection.

24. (new) A gasket for molding a spectacle plastic lens, characterized by comprising

a cylindrical gasket main body in which a first mold with a lens molding surface that forms one lens surface of the spectacle plastic lens and a second mold with a lens molding surface that forms the other lens surface of the spectacle plastic lens are incorporated to be spaced apart from each other at a predetermined gap,

wherein in a portion where at least one of said first mold and said second mold is to be incorporated, an inner circumferential surface of said gasket main body has an inner diameter smaller than an outer diameter of said one mold, and a taper surface that spreads toward an opening side of said gasket main body,

when said one mold is incorporated in said gasket main body, said gasket main body holds said one mold by pressing a circumferential surface of said one mold in a diameter-reducing direction with a restoring force of elastic deformation in a diameter-increasing direction, and the taper surface comes into strongest contact with a circumferential edge on said lens molding surface side of said one mold.

25. (new) A gasket for molding a spectacle plastic lens according to claim 24, characterized in that the taper surface inclines at an angle of 0.5° to 15° with respect to an axis of said gasket main body.

26. (new) A gasket for molding a plastic lens according to claim 24, characterized in that a removal preventive portion which locks with an edge portion of a surface opposite to a

lens molding surface of said one mold integrally projects on an inner circumferential surface of said gasket main body.

27. (new) A gasket for molding a plastic lens according to claim 19, characterized in that said distal end portion is shorter than said proximal end portion.

28. (new) A method for manufacturing a spectacle plastic lens, comprising the steps of forming a spectacle plastic lens molding mold by incorporating, in a gasket, a first mold with a lens molding surface that forms one lens surface of the spectacle plastic lens and a second mold with a lens molding surface that forms the other lens surface of the spectacle plastic lens to be spaced apart from each other at a predetermined gap, and

filling a lens raw material into a cavity of the spectacle plastic lens molding mold, and curing the lens raw material,

characterized in that the gasket includes a cylindrical gasket main body and an elastic projecting band which integrally projects on an inner circumferential wall of the gasket main body throughout an entire circumference,

the projecting band includes a ring-like proximal end portion which projects from the inner circumferential wall of the gasket main body and a tapered distal end portion which is closer to an axial direction of the gasket main body than the proximal end portion, and

the incorporating step comprises the steps of elastically deforming the gasket main body in the diameter-enlarging direction,

holding at least one of the first mold and the second mold by pressing a circumferential surface of said one mold in a diameter-reducing direction with a restoring force of elastic deformation, and

in holding said one mold, causing a vertex of the distal end portion to come into contact with the lens molding surface of said one mold by flexing the proximal end portion.

29. (new) A method for manufacturing a spectacle plastic lens, including the steps of

forming a spectacle plastic lens molding mold by incorporating, in a gasket, a first mold with a lens molding surface that forms one lens surface of the spectacle plastic lens and a second mold with a lens molding surface that forms the other lens surface of the spectacle plastic lens to be spaced apart from each other at a predetermined gap, and

filling a lens raw material into a cavity of the spectacle plastic lens molding mold, and curing the lens raw material,

characterized in that the gasket includes a cylindrical gasket main body,

in a portion where at least one of the first mold and the second mold is to be incorporated, an inner circumferential surface of the gasket main body has an inner diameter smaller than an outer diameter of said one mold, and a taper surface that spreads toward an opening side of the gasket main body, and

the incorporating step comprises the steps of elastically deforming the gasket main body in the diameter-enlarging direction, holding said one mold by pressing a circumferential surface of said one mold in a diameter-reducing direction with a restoring force of elastic deformation, and

in holding said one mold, causing the taper surface to come into strongest contact with a lens molding surface side circumferential edge of said one mold.